

COMMERCIAL

Chest Freezer Solid Top Chest Freezer 38 " Long

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738089 (KCCF073WS)

Solid Top Chest Freezer 38

Short Form Specification

Item No.

Solid top chest freezer with foamed lid and soft closing mechanism to ensure gentle lid closure. Internal and external structure in white painted steel. Basket, vertical basket divider, NSF thermometer and lock included as standard. Defrost water drain with plug for easy cleaning.

R600a refrigerant gas for the lowest environmental impact (GWP=3).

The temperature range is -15° to 10°F.

ETL safety and sanitation listed for US and Canada.

Equipped with NEMA 5-15P plug.

Main Features

- Static Condenser
- 1/6 HP Compressor
- · Mechanical Control
- Internal Temperature Display
- · Freezer Basket
- Locking Lids & Key Protect the contents of the unit
- · Energy Star certified
- Exterior Finish: Textured Painted Steel
- Interior Finish: Painted Steel
- Basket Durable and reliable for safety in food storage (1 basket included).
- ETL®-Certified Temperature Gauge Durable and reliable for safety in food storage.
- Heavy-Duty, Locking Casters Keeps unit in place but allows position adjusting.

Optional Accessories

■ BASKET FOR SOLID TOP 7 CU FT CHEST FREEZER 413X220X428

MM

MM

PNC 882002 □

CHEST FREEZER 413X220X428

APPROVAL:



Chest Freezer Solid Top Chest Freezer 38 " Long

Front U88 EM 37.8in

21.6in

Electric

Supply voltage:

738089 (KCCF073WS) 115 V/1 ph/60 Hz

Electrical power, max: 0.1 kW

Plug type: USA NEMA 5-15P

Key Information:

External dimensions, Width: 37 13/16" (960 mm) **External dimensions, Depth:** 22 1/8" (562 mm) **External dimensions, Height:** 32 11/16" (830 mm) Internal dimensions, Width: 32 1/16 " (814 mm) Internal dimensions, Height: 27 1/4" (692 mm) Internal dimensions, Depth: 14 7/8" (378mm) Net weight: 60 lbs (27.27 kg) Shipping width: 23 1/32" (585 mm) Shipping height: 34 13/16" (885 mm) Shipping weight: 100 lbs (45.36 kg) Shipping volume: 18.37 ft³ (0.52 m³)

Refrigeration Data

Side

Refrigerant type: R600a



El = Electrical connection







