



COMMERCIAL

# Refrigeration Equipment 2-Glass Door Full Height Refrigerator 54" Long

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



738281 (KCHRI54R2GDR) 2-Glass Door Full Height Refrigerator 54" Long

## Short Form Specification

Item No. \_\_\_\_\_

2 glass door refrigerator with exterior back and bottom panels in galvanized steel, exterior side and top panels in 430 stainless steel; interior back, side, top and bottom panels in 304 stainless steel.

Control with cabinet temperature display.

R290 gas in the refrigeration circuit.  
ETL Safety and Sanitation certifications.  
3/5 Years warranty.

## Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Bottom mounted cooling unit slides out for easy access and cleaning.

## Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Lockable door.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.


## Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Interior LED light to save energy and for best internal visibility.

## Optional Accessories

- shelf clips PNC 880611
- SHEET PAN RACK FITS KCHRI MODELS PNC 880622

APPROVAL: \_\_\_\_\_



## Electric

<b>Supply voltage:</b>	
738281 (KCHRI54R2GDR)	115 V/1 ph/60 Hz
<b>Electrical power, max:</b>	0.5 kW
<b>Plug type:</b>	USA NEMA 5-15P

## Key Information:

<b>Capacity (Cu.Ft.)</b>	49
<b>Door hinges:</b>	Right Side
<b>External dimensions, Width:</b>	53 7/8" (1369 mm)
<b>External dimensions, Depth:</b>	31 7/8" (810 mm)
<b>External dimensions, Height:</b>	82 1/4" (2090 mm)
<b>Number and type of doors:</b>	2 Glass
<b>Internal Dimensions (depth):</b>	27 1/16"
<b>Internal Dimensions (height):</b>	60 1/4"
<b>Internal Dimensions (width):</b>	24 7/16"
<b>Shipping height:</b>	84 5/8" (2150 mm)
<b>Shipping weight:</b>	518 lbs (235 kg)
<b>Shipping volume:</b>	92.27 ft <sup>3</sup> (2.61 m <sup>3</sup> )
<b>Number and type of grids (included):</b>	8 - Vinyl-Coated steel
<b>Type of external material:</b>	430 AISI
<b>Type of internal material:</b>	304 AISI
<b>Warranty:</b>	3 / 5 years

## Refrigeration Data

<b>Compressor Horsepower:</b>	1/6
<b>Operating temperature min.:</b>	ISO 9001 °F
<b>Operating temperature max.:</b>	41 °F
<b>Condenser type:</b>	Fin & tube
<b>Defrost type:</b>	Auto Defrost

## Sustainability

<b>Current consumption:</b>	4.5 Amps
<b>Refrigerant type:</b>	R290
<b>Refrigerant weight:</b>	105 g