

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Droi | inct | |
|------|------|--|
| Pro | | |

Model # : Item # :

Qty :

Sandwich/Salad Prep

Super Deluxe Series

Model : TST-72SD-08S-N

Available W/H :

Approval :

Prep Table + Undercounter

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.





Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

Insulated pan cover

Clear lid available (TST-72SD-08S-N-CL)

LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior (ABS door liner) and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place high density, CFC free polyurethane insulation.
- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- Refrigerator holds 33°F ~ 39°F for the best in food preservation

| | | | | | | | (U.S.A only) | |
|----------------|---------------|---------|----------------|-------------|-----|------|-------------------------|---|
| Model | Swing Door | CU./FT. | #of Shelves | #of Pans | HP | AMPS | Crated Weight (lbs.) | $L \ge D \ge T + T + T + T + T + T + T + T + T + T$ |
| TST-72SD-08S-N | 3 | 19 | 3 | 8 | 1/3 | 5.7 | 372 | 725/8 x 30 x 37 |

Ver.20190422

* Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

Prep Table + Undercounter

(unit : inch)

Model : TST-72SD-08S-N

| ELECTRICAL DATA | | | | |
|--|----------------------|--|--|--|
| Voltage | 115/60/1 | | | |
| Plug Type | NEMA 5-15P | | | |
| Full Load Amperes | 5.7 | | | |
| Compressor HP | 1/3 | | | |
| Feed Wires with Ground | 3 | | | |
| Cord Length (ft.) | 9 | | | |
| Refrigerant | R-290 | | | |
| DIMENSIONAL DATA | | | | |
| Ext. Length Overall (in.) | 725/8 (1846mm) | | | |
| Ext. Depth Overall (in.)* | 30 (763mm) | | | |
| Ext. Height Overall (in.) [†] | 37 (940mm) | | | |
| # of Doors | 3 | | | |
| # of Shelves | 3 | | | |
| # of Pans | 8 | | | |
| # of Hood | 1 | | | |
| Net Capacity (cu. ft.) | 19 | | | |
| Chalf Ciza (in) | 21 x 17 (Left/Right) | | | |
| Shelf Size (in.) | 23 x 17 (Middle) | | | |
| Net Weight (lbs.) | 344 | | | |
| Gross Weight (lbs.) | 372 | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

■ WARRANTY : ³ Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included

OPTIONAL ACCESSORIES

- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: M727800100 (Left/Right), M727800300 (Middle)

(GERMAN

KNIFE


- Removable food cover: RCT-72-R
- Stainless steel double overshelf: TSOS-6R
- Door lock: extra lead time will apply, please call factory for more details to order

Ver.20190422



PLAN VIEW

TOP VIEW



SIDE VIEW

Turbo Air : 800-627-0032 **GK** : 800-500-3519

Turbo air Texaking

■ Warranty : 800-381-7770 ■ AC : 888-900-1002

