

GLASS DOOR UNDERCOUNTER REF. NATURAL Refrigerant

Self-Cleaning Condenser Equipped Units

■ **Self-Cleaning Condenser (Patented)**

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ **Digital temperature control & monitor system**

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ **Hydrocarbon refrigerants (R-290)**

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ **Stainless steel cabinet construction**

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a **22 gauge** stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

■ **Sturdy, clean stainless steel shelving**

Shelves are the most important part of cleanliness as they come in direct contact with food. Only the PRO series uniquely provides stainless steel shelving.

■ **Ergonomically designed doors**

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.


■ **High-density polyurethane insulation**

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ **Left hinged model available (PUR-28-G-N-L)**

■ **Spring assisted heavy duty gravity hinge**

■ **Refrigerator holds 33°F ~ 38°F for the best in food preservation**



LED interior lighting & fan control (only at Turbo Air)

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

■ **Standard features**

- Anti-corrosion coated evaporator
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Door locks standard
- Lead time applies

■ **Optional features**

- Legs available for all models: 6" high
- Stainless steel double overshelf available (except PUR-28-G-N)
- Casters available for all models: 1", 2.5", 5"
- Back splash guard available

PUR-G MODELS SPECIFICATIONS ★ New Products

ELECTRICAL DATA	PUR-28-G-N★	PUR-48-G-N★	PUR-60-G-N★	PUR-72-G-N★
Voltage	115/60/1	115/60/1	115/60/1	115/60/1
Plug Type	Ⓢ NEMA 5-15P	Ⓢ NEMA 5-15P	Ⓢ NEMA 5-15P	Ⓢ NEMA 5-15P
Full Load Amperes	6.6	6.5	8.9	9.9
Compressor HP	1/6	1/6	1/6	1/6
Cord Length (ft.)	10	10	10	10
Refrigerant	R-290	R-290	R-290	R-290
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	6.8	12.2	17	18.8
Ext. Dimension (L x D x H) (in.)	27 1/2 x 30" x 30 5/8"†	48 1/4 x 30" x 30 5/8"†	60 1/4 x 30" x 30 5/8"†	72 5/8 x 30" x 30 5/8"†
# of Doors	1	2	2	2
# of Shelves	1	2	2	2
Net Weight (lbs.)	161	248	265	325
Gross Weight (lbs.)	171	260	290	358

Design and specifications subject to change without notice. Most updated spec sheets are available at www.turboairinc.com.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2" for door handles & rear spacers. † Height does not include 5-3/8" for caster height.

■ **WARRANTY: 3 Year Parts and Labor Warranty, Additional 4 Year Warranty on Compressor**